



NOTE: THE OVERLOAD CAPACITIES FOR BENDING MOMENT, AXIAL AND RADIAL FORCE EXCEED 200% OF THOSE USED FOR CROSSTALK MEASUREMENT

SPECIFICATIONS	
CAPACITY (Nm)	200
OVERLOAD CAPACITY (%F.S.)	200
OUTPUT @ F.S. (V) NOMINAL	2.5±2
POWER SUPPLY (V)	5V
BRIDGE RESISTANCE (Ω) NOMINAL	350
NON-LINEARITY (%F.S.)	0.5
HYSTERESIS (%F.S.)	1.0
OPERATING TEMP. RANGE (°C)	-20 TO +100
CROSSTALK (%F.S.)	1.0
AXIAL FORCE FOR CROSSTALK (N)	300
RADIAL FORCE FOR CROSSTALK (N)	500
BENDING MOMENT FOR CROSSTALK (Nm)	55
TORSION ANGLE (CALCULATED)	0.06°
TORSIONAL STIFFNESS (KNm/RAD)	191
BENDING STIFFNESS (KNm/RAD)	60
MASS (KG)	0.30

DRAWING IN THIRD ANGLE PROJECTION

WIRING CODE	
COLOR	FUNCTION
RED	+EX
GREEN	+SIG
BLACK	GND
BROWN	-SIG

**SUNRISE INSTRUMENTS**  
[www.srisensor.com](http://www.srisensor.com)

ROBOT JOINT TORQUE LOADCELL  
 D86MM, 200 Nm

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM	M2212G2	REV. 0.2
--	---------	-------------